

HOT SPOT[®] VC

GALAXY AUDIO

CONTROLLED
BANDWIDTH

COMPACT
VOCAL
MONITOR

HOT SPOT SERIES MONITORS

The HOT SPOT monitor series has been the world's number one personal monitor since its invention in 1977. There are two basic concepts that have led to the continued success of the HOT SPOT. The first concept was to bring the monitor closer to the performer. Second, was to create a monitor that projects mid/high range frequencies; a frequency tailoring that Galaxy calls controlled bandwidth.

By bringing the monitor closer, the stage volume can be reduced, which, in turn, helps clean up the front of house mix. Its integral volume control allows the performer to have more control over his/her volume and to hear the other musicians on stage.

The HOT SPOT's frequency range is tailored for the mid/high range (150Hz-18kHz). As live performers know, the mid/high range carries all the vocal clarity. The HOT SPOT is most effective, because of the fact it can be placed closer to the performer, its use of controlled bandwidth, and most importantly, its two NEOLITE high efficiency high power drivers!

The HOT SPOT features two of Galaxy's new NEOLITE neodymium drivers, each rated at 100 watts continuous. This gives the HOT SPOT its rating of 200 watts @ 16 ohms. The HOT SPOT cabinet is constructed of black high impact ABS and has an attractive cloth grill. The back of the unit features two ¼" input jacks. One serves as the speaker's input; another makes it possible to link multiple HOT SPOTS. The HOT SPOT's front mounted seven position volume control offers 18dB of adjustability (in 3 dB increments). All HOT SPOTS have a built in stand mount which allows them to be easily mounted to a microphone stand.



HOT SPOT[®] VC

GALAXY AUDIO

CONTROLLED
BANDWIDTH

COMPACT
VOCAL
MONITOR

SPECIFICATIONS

Frequency response: 150 Hz –18 kHz

Power handling capacity: 200 Watts

Sensitivity: (1 watt @ 1Meter) 98 dB (1 kHz octave band)

Maximum SPL: (200 watts @ .5 meter): 126 dB

Splowt: 28

Speaker complement: Two NEOLITE Neodymium, ferro fluid cooled 5-inch drivers .86 lbs (.39 kg)

Nominal impedance: 16 ohms

Input connection: Two ¼-inch jacks wired in parallel

Enclosure Materials: High impact ABS plastic

Color: Black case with cloth covered ABS grille

Volume control: 18 dB range;

7 positions at 3 dB each

Optional accessories:

Black vinyl strap handle

SA-1 spun aluminum stand adaptor allows HOT SPOTS to be used on KM style mic stands.

TRANSPORT tote bag

Dimensions: 6.75-inches x 10.94-inches x 6-inches (171 mm x 278 mm x 152 mm)

Net weight: 4.5 lbs. (2.04 kg)

Shipping weight: 6.1 lbs. (2.8 kg)



FerroSound
The Solution is Loud And Clear™

ARCHITECT AND ENGINEER SPECIFICATIONS

The loudspeaker shall be a controlled bandwidth (150Hz - 18kHz) system offering two Neodymium, ferrofluid cooled 5-inch drivers with 7.4-ounce magnet structures. The loudspeaker shall be capable of handling 200 watts continuous. Nominal impedance shall be 16 ohms. Input connection shall be two ¼-inch phone jacks. The enclosure shall be constructed of rugged ABS plastic and feature a cloth covered ABS grille. The cabinet shall be available in black with a black bezel. An integrated flange shall be provided to accommodate microphone stand mounting. An optional handle shall be offered. Dimensions shall be 10.94 inches wide (278 mm), 6.75 inches high (171 mm), and 6 inches deep (152 mm). The system's weight shall be 4.5 lbs (2.04 kg). The loudspeaker system shall be the **GALAXY AUDIO HOT SPOT VC**.

Specifications subject to change without notice.

GALAXY AUDIO

MAKERS OF THE ORIGINAL HOT SPOT PERSONAL MONITOR

601 E. Pawnee Wichita, KS 67211 316.263.2852 FAX 316.263.0642 www.galaxyaudio.com

Distributed outside the United States by **E and E Exports, Inc.** 17922 Sky Park Circle, Suite P, Irvine, CA 92714 949.440.0760 FAX 949.440.0766

Distributed in Canada by **Cable Tek/JP Cabletek Electronics, Ltd.** 1638 Kebet Way Building 100 Port Coquitlam, BC V3C 5W9 604.942.1001 FAX 604.942.1010