

# Sx80BE

## Sx/Sb Series™ Speaker System

Ultracompact two-way 8-inch system with 175 watts continuous, 700 watts peak power handling | EV DH2005 pure titanium compression driver for great sound and reliable performance | 90° x 65° constant-directivity high-frequency horn | Paintable, black polystyrene enclosure | Single Neutrik Speakon® connector | Available in paintable white(Sx80WE) | Suspension points accommodate Sx80MBB and Sx80MBW wall/ceiling brackets and OmniMount® Series 75 mounting hardware (OmniMount is a registered trademark of OmniMount Systems, Inc.) | Optional Sx80SM stand-mount adapter accepts 100BK stand

### Specifications

Frequency Response (-10dB)	51 - 20000 Hz
Sensitivity 1W/1m	92 dB
Max. SPL / 1m (calc); full space	121 dB
Coverage (nominal -6dB) H°	90 °
Coverage (nominal -6dB) V°	60 °
System Power Handling (continuous/program/peak)	175/350/700 Watts
HF Transducer	DH2005
Crossover Frequency	2200 Hz
Nominal Impedance (Passive)	8 Ohms
Minimum Impedance	7.2 Ohms
Color	Black
Color	White
Directivity Index	9.2 dB
Flying	Yes
Chassis Size	8 inches
Speaker Type	Fullrange, Mid-High, Two-Way
Weight Net	8.2 kg ( 18.08 lbs )
Dimensions (HxWxD)	400 x 292 x 222 mm (15.75" x 11.5" x 8.74")



### **Related Press Releases**

[EV ADDS VENOM TO KOLKATA, INDIA, CLUB](#)

[EV PROVIDES PREMIUM PUB AUDIO IN INDIA](#)

[DAVID LETTERMAN'S HIGH SCHOOL STEPS UP TO EV](#)

[EVIDS WORK OUT AT THE GYM](#)

[STATE OF THE ART SYNAGOGUE GOES WITH EV](#)

### **Downloads**

[Sx80BE EDS](#)

[Sx80BE High-Res Image](#)

### **Accessories**



[DYNACORD](#) | [DYNACORD ProAnnounce](#) | [Electro-Voice](#)  
| [IRISnet](#) | [Klark Teknik](#) | [Midas](#) | [Telex](#)

### **[Sx80MB](#)**

Wall/Ceiling Mounting Bracket for Sx80.